

flow rate of gas circulating between an inner circumference of the hollow capillary and an outer circumference of the resistance adjusting rod by adjusting a circulation resistance of the gas, wherein the circulation resistance can be adjusted by varying an insertion length of the resistance adjusting rod inserted into the hollow capillary, and wherein and can be fixed by fitting a separation preventing short tube is fitted to an outer circumference of the hollow capillary at an opening end, the separation preventing short tube being fitted to prevent movement of the adjusting rod and thereby fix the circulation resistance.

Claim 4 (currently amended): The vacuum control system according to claim 1, wherein the air introduction device comprises a constant circulation resistance tube which is formed by coaxially inserting a resistance adjusting rod into a hollow capillary and which can control a flow rate of gas circulating between an inner circumference of the hollow capillary and an outer circumference of the resistance adjusting rod by adjusting a circulation resistance of the gas, wherein the circulation resistance can be adjusted by varying an insertion length of the resistance adjusting rod inserted into the hollow capillary, and wherein and can be fixed by fitting a separation preventing short tube is fitted to an outer circumference of the hollow capillary at an opening end, the separation preventing short tube being fitted to prevent movement of the adjusting rod and thereby fix the circulation resistance.

Claim 5 (currently amended): A vacuum degassing apparatus for removing dissolved gas from liquid isolated ~~with a gas permeation diaphragm, comprising:~~

~~a vacuum vessel~~ by reducing the inside pressure of a vacuum vessel including a ~~the~~ gas permeation diaphragm;

[[with]] an exhaust vacuum pump; and

~~a, the vacuum degassing apparatus employing the vacuum control system according to~~
~~claim 1, the vacuum control system including:~~

a controller for monitoring the inside pressure of the vacuum vessel using a pressure sensor, and controlling a voltage applied to a DC brushless motor on the basis of an output signal resulting from measurement of the inside pressure of the vacuum vessel by the pressure sensor to control the displacement of the exhaust vacuum pump; and

an air introduction device inserted in a vacuum exhaust path provided by a vacuum exhaust pipe that interconnects the vacuum vessel to the exhaust vacuum pump, the air introduction device being inserted in the vacuum exhaust path at a position on the vacuum exhaust pipe between the vacuum vessel and the exhaust vacuum pump, for continuously introducing a controlled amount of air into the vacuum exhaust pipe, wherein

gas dissolved in the liquid is isolated with the gas permeation diaphragm by reducing the inside pressure of the vacuum vessel by operating the exhaust vacuum pump, and by operating the controller to hold the degree of vacuum in the vacuum vessel constant.

Claim 6 (canceled).

Claim 7 (currently amended): The vacuum degassing apparatus according to claim 5, wherein the air introduction device comprises a constant circulation resistance tube which is

formed by coaxially inserting a resistance adjusting rod into a hollow capillary and which can control a flow rate of gas circulating between an inner circumference of the hollow capillary and an outer circumference of the resistance adjusting rod by adjusting a circulation resistance of the gas, wherein the circulation resistance can be adjusted by varying an insertion length of the resistance adjusting rod inserted into the hollow capillary, and wherein and can be fixed by fitting a separation preventing short tube is fitted to an outer circumference of the hollow capillary at an opening end, the separation preventing short tube being fitted to prevent movement of the adjusting rod and thereby fix the circulation resistance.

Claim 8 (new): The constant circulation resistance tube of claim 3, wherein the constant circulation resistance tube is configured such that the circulating gas flows along substantially the entire length of the resistance adjusting rod within the hollow capillary.

Claim 9 (new): The constant circulation resistance tube of claim 3, wherein a waste inflow preventing filter is fitted to an opening of the separation preventing short tube.